



ORDER FORM

PYRO START PLUS

Light weight wheelchair

Company:

Basic price: **Pyro Start Plus without drum brake** € 999,-

Basic price: **Pyro Start Plus with drum brake** € 1.198,-

Customer:

Max. capacity 125 kg

Date:

▼ Please mark!

Seat	€
Seat width in mm	
370 400 430 460 490	○
520	38,-
Seat height front in mm	
500	○45,50
425 450 475	
Seat depth adjustable from 400 - 440 mm	●
Seat cushion Seat width 370 - 460 mm	24,-
Seat cushion Seat width 490 mm	26,-
Seat cushion Seat width 520 mm	30,-
Seat upholstery, Nylon	●
Back support	
Back support adjustable 420 - 440 mm	●
Back support with lumbar curve	●
Back support adjustable by strap-system	153,50
Head support* incl. fixation	188,-
Handgrip elevating*, removable Pair	152,40
Back support upholstery, Nylon	●
Sidepanels	
Sidepanel removable with arm support, swing-away, elevating	●
Sidepanel elevating left right	108,20
Sidepanel elevating with foldable arm pads left right	123,50
Leg support	
Swing-away leg support with individual footplates plastic, removable, adjustable in height	●
Leg support elongation 100 mm Pair	60,80
Lower leg support elevating left right	107,60
Amputee support left right	157,-
Footplates with heel straps	●

▼ Please mark!

Tyres	€
Rear wheels 24" x 1 3/8" PU incl. quick-release axle	●
Front wheels 8" x 1 1/4", PU	●
Wheel base extension	●
Adapter block	●
Front wheels 200 x 50 mm. PU Pair	60,80
Spoke protection, transparent 24"	145,-
One arm drive only without drum brake left right	325,-
Hand rim rubber-coated 24" Pair	110,-
Wheel locks	
Knee lever wheel lock push to lock	●
Wheel lock lever extension	23,-
Knee lever wheel lock for one-arm drive left right	88,60
Accessories	
Togo power push aid incl. mounting set	2.446,60
Mounting aid for adaptation	189,50
Anti-tip device Pair	87,50
Tilting aid	●
Safety belt	26,80
Crutch holder	23,70
Therapy tray	215,-
Oxygen/infusion holder and bracket	169,-
APINO Shopper	18,20
Passive light	●
Frame colour	
Silver	●

* Head support and handgrips elevating cannot be mounted together

The specified dimensions are subject to manufacturing tolerances of +/- 10 mm

● Basic equipment

○ Optional, no extra charge